

**Product Description** Prospray® PMC-3000™ Matte Clearcoat is a two-component flat clear designed to dry to a matte finish while still providing excellent durability. PMC-3000 offers excellent spray characteristics, is ideal for use when it is necessary to match a matte, OEM finish and is also excellent for custom “flat” paint jobs.

### Components



Clear  
Activators  
Thinners

**PMC-3000™**  
**ICA series 799-803**  
**ICR series 1692-1695**

### Substrates

- Prospray Basecoat
- R-6028 Basecoat Blender
- Sanded OE Clearcoat

### Surface Preparation



Mask entire vehicle to eliminate unwanted overspray.

### Mix Ratio

Refer to “Activator and Thinner Selection Guide - NATIONAL RULE”.

Clear  
Activator  
Thinner



2 Parts  
1 Part  
up to 10%

**NOTE: Product may settle. Shake thoroughly before use.**

### Gun Set Up



**High Efficiency**    **HVLP**  
1.2mm–1.4mm    1.2mm–1.4mm

### Pot Life @ 72°F / 22.2°C



1 hour

### Viscosity @ 72°F / 22.2°C

12–13 secs DIN4

### Air Pressure



**High Efficiency**

15–29 psi @ the gun

**HVLP**

6–10 psi max @ the cap

**NOTE: Refer to individual gun manufacturer for proper spray gun setting**

### Application



- 2 coats
- 10–15 minutes flash between coats

# Matte Clearcoat

## PMC-3000

### Flash/Dry Times @ 72°F / 22.2°C



#### **Air Dry**

**Flash between coats:** 10 – 15 minutes

**Dust free:** 30 minutes

**Time to assemble:** 2 – 3 hours

#### **Force Dry**

30 minutes @ 140°F/60°C

### Blending

Not recommended

### Polishing



**Sanding:** N/A

**Compounding:** N/A

### Special Notes / Clean Up



**Clean Up** Clean equipment after use with a cleaning solvent. Dispose of solvent according to state, local and federal regulations.

### Physical Data

**VOC (RTS) per U.S. Gal** 3.65 lbs/gal, 438.42 g/l

### Health and Safety



For professional use only. KEEP OUT OF REACH OF CHILDREN. WARNING! CONTENTS ARE FLAMMABLE. VAPOR AND SPRAY MIST IS HARMFUL. SKIN AND EYE IRRITANT.

Do not handle the Prospray products until the Material Safety Data Sheets have been read and understood in their entirety. Ensure that all employees are trained on Material Safety Data Sheets and all chemicals with which they come into contact. The manufacturer recommends the use of an air-supplied respirator when exposed to vapors or spray mist. Wear protective clothing, gloves and eye safety with a side shield.

This data sheet information is given in good faith but without warranty. The information contained herein represents the current state of our knowledge and is intended as a guide to our products and their uses; it is not intended for insurance of certain product properties or of their specific applications.

Follow all warnings on product labels.