

Kicker 2K Accelerator LV-497

A Valspar Automotive Brand
600 Nova Drive SE • Massillon, Ohio 44646
ProsprayFinishes.com

Technical Support: 1-800-776-0933

Product Description Prospray® LV-497™ Low VOC Kicker 2K Accelerator improves productivity by accelerating the dry time of Prospray low VOC clearcoats, low VOC single stage color and low VOC 2K primers.

Do not use LV-497 in DTM, epoxy, etch primer or 1K products.

Components

**LV-497**

Mix Ratio

Recommended: Use 20 ml of LV-497 Low VOC Kicker 2K Accelerator per sprayable quart of the following:
(Ready to Spray) **2.8 VOC single stage color, 2.1 VOC clearcoats, 2.1 VOC 2K primers**

Special Notes / Clean Up



NOTE: Do not use LV-497 in DTM, epoxy, etch primer or 1K products.

Clean Up Clean equipment after use with a Low VOC cleaning solvent. Dispose of solvent according to state, local and federal regulations.

Health and Safety



For professional use only. KEEP OUT OF REACH OF CHILDREN. WARNING! CONTENTS ARE FLAMMABLE. VAPOR AND SPRAY MIST IS HARMFUL. SKIN AND EYE IRRITANT.

Do not handle the Prospray products until the Safety Data Sheets have been read and understood in their entirety. Ensure that all employees are trained on using the Safety Data Sheets and all chemicals with which they come into contact. The manufacturer recommends the use of an air-supplied respirator when exposed to vapors or spray mist. Wear protective clothing, gloves and eye safety with a side shield.

This data sheet information is given in good faith but without warranty. The information contained herein represents the current state of our knowledge and is intended as a guide to our products and their uses; it is not intended for insurance of certain product properties or of their specific applications.

Follow all warnings on product labels.