

Plasticizing Additive PLV-2020


A Valspar Automotive Brand
600 Nova Drive SE • Massillon, Ohio 44646
ProsprayFinishes.com

Technical Support: 1-800-776-0933

Product Description PLV-2020™ Low VOC Plasticizing Additive is formulated to enhance the flexibility of low VOC 2K clearcoats, low VOC 2K undercoats, low VOC single stage color and 3.5 VOC basecoat color when used over semi-flexible and flexible parts.

Mix Ratios

Semi-Flexible Plastics



5 Parts: *Mixed* **Low VOC 2K undercoats, low VOC clearcoats, Low VOC single stage color or 3.5 VOC basecoat color**
1 Part: **PLV-2020**

Flexible Plastics



2 Parts: *Mixed* **Low VOC 2K undercoats, low VOC clearcoats or low VOC single stage color**
1 Part: **PLV-2020**

PLV-2020 should only be added to **3.5 VOC Intermix System Basecoat** when used over very flexible plastics.



3 Parts: **3.5 VOC Intermix System Basecoat**
1 Part: **PLV-2020***

* **NOTE:** Always add PLV-2020, then activate and thin as normal.
Do not add PLV-2020 to H2O basecoat.

Health and Safety



For professional use only. KEEP OUT OF REACH OF CHILDREN. WARNING! CONTENTS ARE FLAMMABLE. VAPOR AND SPRAY MIST IS HARMFUL. SKIN AND EYE IRRITANT.

Do not handle the Prospray products until the Safety Data Sheets have been read and understood in their entirety. Ensure that all employees are trained on using the Safety Data Sheets and all chemicals with which they come into contact. The manufacturer recommends the use of an air-supplied respirator when exposed to vapors or spray mist. Wear protective clothing, gloves and eye safety with a side shield.

This data sheet information is given in good faith but without warranty. The information contained herein represents the current state of our knowledge and is intended as a guide to our products and their uses; it is not intended for insurance of certain product properties or of their specific applications.

Follow all warnings on product labels.