

Item Code	Product Name	Shelf Life (in years)*
A-116	Medium Basecoat Thinners	5
A-118	2K Universal Medium Thinner	5
A-119	2K Universal Fast Thinner	5
A-300	H.S. Primer - Grey	2
A-380	Matting Agent	2
A-497	2 Component Accelerator	2
A-500	Extra Build-Easy Sand Primer Grey	2
A-514	Etch Primer	2
A-516	Etch Primer Activator	2
A-524	Plastic Bumper Primer Clear (RTS)	3
A-700	2K H.S. Extra Build / Easy Sand Primer Surfacer - Grey	2
A-702	2K H.S. Extra Build / Easy Sand Primer Surfacer - White	2
A-704	2K H.S. Extra Build / Easy Sand Primer Surfacer - Black	2
A-706	Black Tint Concentrate	2
AB-810	H.S. Bright Medium Aluminum	2
AB-814	H.S. Fine Aluminum	2
AB-816	H.S. Medium Aluminum	2
AB-818	H.S. Medium Coarse Aluminum	2
AB-821	H.S. Coarse Aluminum	2
AB-832	H.S. Very Coarse Aluminum	2
AB-841	Shining Coarse Aluminum	2
AB-842	Silver Dollar Coarse Aluminum	2
AB-844	Fine Satin Aluminum	2
BCB-005	Basecoat Flip Control	2
BCB-051	Mixing Basecoat Binder	2
BCB-061	Mixing Scheme Basecoat Binder	2
BCB-600	Basecoat Balancer	2
BCB-825	Basecoat Flip Control H.S.	2
EBA-50	Engine Bay Adjuster	2
EBB-20	Engine Bay Binder	2
HB-500	H.S. Super White	2
HB-511	H.S. Claret	2
HB-512	H.S. Lagoon Blue	2
HB-545	H.S. Strong Red	2
HB-546	H.S. Black	2
HB-547	H.S. Jet Black	2
HB-551	H. S. Blue Green	2
HB-552	H.S. Fast Blue	2
HB-570	H.S. Brilliant Red	2
ICA-601	FCC Normal Activator	2
ICA-602	FCC Express Activator	2
ICA-660	Normal Activator	2
ICA-690	Express Activator	2
ICA-800	M.S. Slow Activator	2
ICA-801	M.S. Normal Activator	2
ICA-802	M.S. Express Activator	2
ICA-803	M.S. Rapid Activator	1
ICC-6000	Fast Cure Clear	2
ICC-8000	H.S. Multi Clear	2
ICR-1401	Fade Out Thinner	5
ICR-1492	Medium Basecoat Thinners	5
ICR-1692	2K H.S. Fast Thinner	5
ICR-1693	2K H.S. Medium Thinner	5
ICR-1694	2K H.S. Slow Thinner	5
MB-201	Pale White	2
MB-203	Transparent Black	2

* The shelf life applies to unopened containers that are stored under normal storage conditions between 5-30°C / 41-86°F.

Item Code	Product Name	Shelf Life (in years)*
MB-204	Yellow Oxide	2
MB-205	Trace Yellow	2
MB-206	Red Oxide	2
MB-207	Russet	2
MB-209	Deep Blue	2
MB-219	Violet	2
MB-224	Super Red	2
MB-229	Blue Lake	2
MB-231	Blue Black	2
MB-237	Tone Controller	2
MB-240	Transoxide Red	2
MB-251	Fast Blue	2
MB-259	Burgundy	2
MB-272	Cyan Blue	2
MB-273	Bronze Green	2
MB-275	Strong Maroon	2
MB-276	Brown	2
MB-277	Fast Maroon	2
MB-278	Transoxide Yellow	2
MB-279	Strong Yellow	2
P-2020	Plasticising Additive	2
PB-780	Pearl White	2
PB-781	Fine Pearl White	2
PB-782	Pearl Blue	2
PB-783	Red Pearl	2
PB-784	Pearl Gold	2
PB-785	Copper Pearl	2
PB-786	Pearl White Ultrafine	2
PB-787	Pearl Red Fine	2
PB-788	Russet Pearl Fine	2
PB-789	Pearl Blue Fine	2
PB-790	Pearl Violet Medium	2
PB-791	Pearl Green Medium	2
PB-792	H.S. Blue Frost	2
PB-793	Graphite Flake	2
PB-794	Gold Flash	2
PB-795	Orange Aluminum	2
PB-796	Super Orange Pearl	2
PSC-5000	Scratch Resistant Hyper Clear	2
PSC-7000	Universal Clear	2
PSE-1001	Crystal Silver	2
PSE-1002	Sunbeam Gold	2
PSE-1003	Radiant Red	2
PSE-1004	Galaxy Blue	2
PSE-1005	Stellar Green	2
PSE-1006	Solaris Red	2
PSE-1007	Fireside Copper	2
PSE-1008	Cosmic Turquoise	2
PSE-1009	Amethyst Dream	2
PSE-1010	Viola Fantasy	2
PSE-1011	Arctic Fire	2
PSE-1012	Tropic Sunrise	2
PSE-1013	Autumn Mystery	2
PSE-3001	Silver to Green	2
PSE-3002	Gold to Silver	2
PSE-3003	Green to Purple	2

* The shelf life applies to unopened containers that are stored under normal storage conditions between 5-30°C / 41-86°F.

Item Code	Product Name	Shelf Life (in years)*
PSE-3004	Cyan to Purple	2
PSE-3005	Blue to Red	2
PSE-3006	Magenta to Gold	2
R-6028	Basecoat Blender	2
SCB-240	Medium Premium Binder	2
SCB-408	Single Layer Binder	2
SCB-673	Single Layer Adjuster	2
SCBC-574	Solid Color Basecoat Converter	2
VB-602	Bright Maroon	2
VB-604	Pale Yellow	2
VB-605	Basecoat Jet Black	2
VB-606	H.S. Orange Red	2
VB-607	Brilliant Orange	2
VB-610	Medium Yellow	2
VB-615	Ultra Jet Black	2
VB-618	Yellow	2
VB-619	Pure Magenta	2
VB-620	H.S. Red Violet	2
VB-624	H.S. Speed Red	2
W820	Antistatic Degreaser	5

* The shelf life applies to unopened containers that are stored under normal storage conditions between 5-30°C / 41-86°F.